

**CHASSIS TYPE:
23 1/2' STRAIGHT FRAME
EXTENDABLE CONTAINER CHASSIS (SLIDER)**



GENERAL PARAMETERS

| | |
|--------------------------------|--|
| Tare Weight | Approximately 6,600 lbs |
| GVWR | 54,000 lbs |
| Twist Locks | 4-Pin |
| Conspicuity | Meets DOT requirements |
| Main Beams | Wide flange I-beam 12 in deep, 19 lb/ft, hot rolled steel, ASTM A572-50 |
| Upper Coupler Assembly | Pick up plate is 5/16 in thick and extends appx 33 in behind kingpin |
| Front Bolster | Box type w 3/8 in x 8 in top plate and 1/4 in thick, formed channel lower member |
| ICC Bumper | 4 in x 4 in x 3/16 in tube step bumper |
| Mud Flaps | Plastic anti-sail |
| Electrical System | 12 volt, 7-way split pin receptacle plug; modular wiring harness |
| Slider Mechanism | Lock engagement ensured by two spring-loaded pins through main beams |
| Overall length Closed/Extended | Closed 23'x3" / Extended 26'x11" |
| Overall Chassis Width, Length | 96" x 52 1/2" |
| Light Attachment, Type | Flange mounted, LED |

LANDING GEAR

| | |
|-------------------------|---|
| Landing Gear | Just 2-speed AAR approved, square leg. 55,000 lb lift capacity and 160,000 static load capacity |
| Landing Gear Foot Group | 10 in. by 10 in. low profile sandshoe |
| Crank Handle Location | Curb side handle |

BRAKES

| | |
|-----------------------------------|------------------|
| Drum | Outboard mounted |
| Brake Lining Options, System Type | Standard, 2S1M |

WHEELS

| | |
|--------------------|------------------------------------|
| Rims | 8 1/4 X 22.5 hub piloted tubeless |
| Tires | 11R/22.5 |
| Hub Type, Material | Hub piloted for disc wheels, steel |

AXLES

| | |
|------------------|-----------------------------|
| Axle Quantity | 2 Axles |
| Axle Type | TN |
| Kingpin Location | 15 in from front of chassis |

SUSPENSION

| | |
|-----------------|-------------|
| Suspension Type | Spring-ride |
| Springs | Three leafs |

ADD-ONS

| | |
|---------------------|---------------------------------|
| Customer Decals | Furnished by Customer |
| Registration Holder | Plastic with clear screw on top |

FINISH

| | |
|-------------------|--|
| Metal Preparation | Clean, dry steel and NACE No. 3 /SSPC-SP-6 "Commercial Blast Cleaning" |
| Primer | 70% Zinc Rich Primer |
| Topcoat | Urethane Topcoat |
| Color | Black |



8803 Highway 225
La Porte, Texas, USA 77571
www.TankService.com
Sales: 713-665-3001